

10mm Auto

.400"	40 TMJ® FN	40 GDHP	
Weight (grains)	155	155	
Ballistic Coefficient	0.125	0.123	
Sectional Density	0.138	0.138	
COAL Tested	1.250"	1.250"	
Speer Part No.	4399	4400	

			START CHARGE		MAXIMUM CHARGE	
Propellant	Case	Primer	Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Accurate No. 7	Hornady	CCI 300	12.0	1187	13.0	1320
Alliant Blue Dot	Hornady	CCI 300	11.0	1164	12.0	1291
Alliant Unique	Hornady	CCI 300	7.5	1091	8.5	1246
Hodgdon HS-6	Hornady	CCI 350	9.5	1095	10.5	1223
Winchester 231	Hornady	CCI 300	7.0	1062	7.7	1183
Vihtavuori N340	Hornady	CCI 300	7.2	1034	8.0	1180
Accurate No. 5	Hornady	CCI 300	9.2	1004	10.2	1176
Winchester WSF	Hornady	CCI 300	7.6	1017	8.4	1162

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load