

## 357 Magnum

.357"	38 JHP
Weight (grains)	110
Ballistic Coefficient	0.113
Sectional Density	0.123
COAL Tested	1.575"
Speer Part No.	4007

NOTE: Do not use the 110-grain Gold Dot SB HP (#4009) in the 357 Magnum.

			START CHARGE		MAXIMUM CHARGE	
Propellant	Case	Primer	Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Vihtavuori N110	Speer	CCI 500	19.0	1557	21.0 C	1693
Alliant 2400	Speer	CCI 500	17.5	1536	19.5	1670
Alliant Power Pistol	Speer	CCI 500	9.5	1326	10.5	1451
Alliant Unique	Speer	CCI 500	8.5	1284	9.7	1447
Vihtavuori 3N37	Speer	CCI 500	9.7	1305	10.8	1433
Alliant Bullseye	Speer	CCI 500	7.8	1246	8.7	1403
Hodgdon Hi-Skor 700-X	Speer	CCI 500	7.0	1208	8.0	1366
Hodgdon H. Universal	Speer	CCI 500	8.0	1264	9.0	1359
Accurate No. 5	Speer	CCI 500	10.8	1246	12.0	1330
Winchester 231	Speer	CCI 500	8.5	1231	9.5	1319

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load