



## 357 Magnum

<b>.357"</b>	<b>38</b>
	<b>GDHP SB</b>
<b>Weight (grains)</b>	135
<b>Ballistic Coefficient</b>	0.141
<b>Sectional Density</b>	0.151
<b>COAL Tested</b>	1.590"
<b>Speer Part No.</b>	4014

**SHORT BARREL VELOCITIES**  
 Test Firearm: S&W Model 19 2.5"

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Accurate No. 9	Speer	CCI 500	14.5	1202	<b>15.5</b>	1258
Hodgdon H110	Speer	CCI 550	17.5	1128	<b>18.5</b>	1205
Alliant 2400	Speer	CCI 500	15.0	1124	<b>16.0</b>	1176
Alliant Power Pistol	Speer	CCI 500	8.6	1046	<b>9.6</b>	1137
Winchester 296	Speer	CCI 550	17.5	1105	<b>18.5</b>	1130
Alliant Unique	Speer	CCI 500	6.8	971	<b>7.8</b>	1109
Vihtavuori 3N37	Speer	CCI 500	7.7	874	<b>8.7</b>	1012

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*