

38 Special +P

.357"	38 JHP	38 GDHP SB
Weight (grains)	110	110
Ballistic Coefficient	0.113	0.117
Sectional Density	0.123	0.123
COAL Tested	1.455"	1.455"
Speer Part No.	4007	4009

			START CHARGE		MAXIMUM CHARGE	
Propellant	Case	Primer	Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Power Pistol	Speer	CCI 500	7.0	1123	7.4	1192
Vihtavuori 3N37	Speer	CCI 500	6.9	1071	7.3	1150
Accurate No. 5	Speer	CCI 500	7.5	1099	7.9	1143
Alliant Unique	Speer	CCI 500	5.9	1090	6.3	1117
Hodgdon H. Universal	Speer	CCI 500	5.7	1028	6.1	1100
Alliant Bullseye	Speer	CCI 500	4.8	1027	5.2	1098
Hodgdon Hi-Skor 700-X	Speer	CCI 500	4.7	1017	5.1	1085
Hodgdon TITEGROUP	Speer	CCI 500	4.7	1013	5.1	1082
Winchester 231	Speer	CCI 500	5.2	1008	5.6	1059
Alliant American Select	Speer	CCI 500	4.4	894	4.8	967

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load