



45 Automatic

.451"	45 TMJ® Match SWC	45 GDHP
Weight (grains)	200	200
Ballistic Coefficient	0.128	0.138
Sectional Density	0.140	0.140
COAL Tested	1.275"	1.200"
Speer Part No.	4475	4478

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant BE-86	Federal	Federal 150	6.0	825	8.1	1083
Winchester AutoComp	Federal	Federal 150	6.2	834	8.1	1076
Hodgdon CFE Pistol	Federal	Federal 150	6.1	824	8.1	1067
Alliant Unique	Federal	Federal 150	6.5	927	7.3	1057
Hodgdon HS-6	Federal	Federal 150	8.5	944	9.5	1054
Alliant Blue Dot	Federal	Federal 150	9.4	917	10.5	1048
Accurate No. 7	Federal	Federal 150	9.9	912	11.0	1037
Alliant Power Pistol	Federal	Federal 150	7.0	874	8.3	1026
Hodgdon H. Universal	Federal	Federal 150	6.3	905	7.0	1018
Accurate No. 5	Federal	Federal 150	8.1	916	9.0	1013
Winchester WSF	Federal	Federal 150	6.4	894	7.2	1004
Alliant Sport Pistol	Federal	Federal 150	4.8	779	6.3	993
Alliant Bullseye	Federal	Federal 150	5.2	864	5.8	957
Vihtavuori N340	Federal	Federal 150	6.3	814	7.0	947
Vihtavuori 3N37	Federal	Federal 150	7.3	794	8.2	942
Winchester 231	Federal	Federal 150	5.6	826	6.3	931

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load