

480 Ruger

.475"	475 DCSP
Weight (grains)	325
Ballistic Coefficient	0.191
Sectional Density	0.206
COAL Tested	1.650"
Speer Part No.	3978

			START CHARGE		MAXIMUM CHARGE	
Propellant	Case	Primer	Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon H. Lil' Gun	Hornady	CCI 350	26.0	1427	28.0	1492
Winchester 296	Hornady	CCI 350	26.0	1366	28.0	1464
Vihtavuori N110	Hornady	CCI 300	22.5	1349	24.5 C	1457
Hodgdon H110	Hornady	CCI 350	26.0	1368	28.0	1445
Accurate No. 9	Hornady	CCI 300	23.0	1360	25.0	1444
Alliant 2400	Hornady	CCI 300	23.0	1319	25.0	1435
IMR 4227	Hornady	CCI 300	27.0 C	1263	29.0 C	1389
Accurate 1680	Hornady	CCI 350	28.0	1138	30.0 C	1239
Alliant Unique	Hornady	CCI 300	10.0	991	13.0	1178

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load