

7-30 Waters (Handgun)

.284"	7mm Spitzer SP Hot-Cor®	7mm Spitzer BTSP	
Weight (grains)	130	130	
Ballistic Coefficient	0.368	0.424	
Sectional Density	0.230	0.230	
COAL Tested	2.550"	2.550"	
Speer Part No.	1623	1624	

			START CHARGE		MAXIMUM CHARGE	
Propellant	Case	Primer	Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 15	Federal	CCI 200	31.5	2037	35.5	2327
Winchester 748	Federal	CCI 250	31.0	2005	35.0	2304
Hodgdon H4895	Federal	CCI 200	30.0	2022	34.0	2294
IMR 3031	Federal	CCI 200	29.0	1967	33.0	2264
Vihtavuori N135	Federal	CCI 200	28.5	1969	32.5	2260
Hodgdon H335	Federal	CCI 250	29.0	1996	33.0	2212
Accurate 2015	Federal	CCI 200	26.0	1976	30.0	2208
Accurate 2230	Federal	CCI 250	26.0	1951	30.0	2188
Alliant Reloder 7	Federal	CCI 200	23.0	1914	27.0	2137

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load