



222 Remington Magnum

.224"	22 TNT® Green®	22 Spitz SP	22 TNT® HP
Weight (grains)	50	50	50
Ballistic Coefficient	0.190	0.207	0.228
Sectional Density	0.142	0.142	0.142
COAL Tested	2.250"	2.250"	2.250"
Speer Part No.	1028	1029	1030

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon H335	Remington	CCI 450	26.5	3250	28.5	3522
IMR 4320	Remington	CCI 400	27.0	3262	29.0	3490
IMR 4198	Remington	CCI 400	21.0	3138	23.0	3423
IMR 4064	Remington	CCI 400	26.0	3196	28.0	3422
Hodgdon BL-C(2)	Remington	CCI 450	25.0	3196	27.0	3405
IMR 3031	Remington	CCI 400	24.5	3155	26.5	3403
Hodgdon H414	Remington	CCI 450	29.0	3139	31.0	3388
IMR SR 4759 (reduced load)	Remington	CCI 400	9.0	1690	11.0	2077

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load