

222 Remington

| .224" | 22 TNT Green® |
|-----------------------|---------------------|
| Weight (grains) | 50 |
| Ballistic Coefficient | 0.190 |
| Sectional Density | 0.142 |
| COAL Tested | 2.100" |
| Speer Part No. | 1028 |

| | | | START CHARGE | | MAXIMUM CHARGE | |
|---------------------------|---------|-------------|-----------------|-------------------------------|-----------------|----------------------------|
| Propellant | Case | Primer | Weight (grains) | Muzzle Velocity (feet/sec) | Weight (grains) | Muzzle Velocity (feet/sec) |
| Alliant AR-Comp | Federal | Federal 205 | 20.3 | 2896 | 22.2 C | 3094 |
| Alliant Power Pro Varmint | Federal | Federal 205 | 22.0 | 2915 | 23.8 | 3087 |
| Alliant Power Pro 1200-R | Federal | Federal 205 | 19.1 | 2827 | 21.1 | 3078 |
| Winchester 748 | Federal | Federal 210 | 21.5 | 2849 | 23.5 | 3066 |
| Vihtavuori N133 | Federal | Federal 210 | 18.0 | 2831 | 20.0 | 3063 |
| Hodgdon BENCHMARK | Federal | Federal 210 | 19.5 | 2796 | 21.5 | 3062 |
| IMR 3031 | Federal | Federal 210 | 19.0 | 2782 | 21.0 C | 3053 |
| Ramshot X-Terminator | Federal | Federal 210 | 20.0 | 2818 | 22.0 | 3044 |
| Hodgdon CFE 223 | Federal | Federal 205 | 22.4 | 2845 | 24.4 | 3038 |
| Alliant Relodr 10X | Federal | Federal 205 | 18.5 | 2722 | 20.4 | 2980 |
| Accurate LT-30 | Federal | Federal 205 | 17.2 | 2698 | 19.0 | 2940 |

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load