



223 Remington

.224"	22 GD
Weight (grains)	62
Ballistic Coefficient	0.310
Sectional Density	0.177
COAL Tested	2.230"
Speer Part No.	22462GDB

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Power Pro 2000-MR	Federal	Federal 205	25.0	2969	27.7 C	3217
Hodgdon CFE 223	Federal	Federal 205	23.4	2889	26.0	3141
Alliant Power Pro Varmint	Federal	Federal 205	22.0	2864	24.3	3076
Ramshot X-Terminator	Federal	Federal 205	21.7	2838	23.9	3071
Accurate 2460	Federal	Federal 205	22.3	2815	24.8	3069
Hodgdon Varget	Federal	Federal 205	22.4	2802	24.9 C	3064
IMR 8208 XBR	Federal	Federal 205	21.4	2822	23.7	3064
IMR 4895	Federal	Federal 205	22.3	2759	24.8 C	3064
Alliant Reloder 15	Federal	Federal 205	22.7	2808	25.1 C	3056
Alliant AR-Comp	Federal	Federal 205	20.8	2826	23.0	3030
Vihtavuori N540	Federal	Federal 205	22.4	2746	24.8	3009
Hodgdon H335	Federal	Federal 205	20.3	2770	22.4	2971

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load