

22 Hornet

0.224"	22 TNT® HP
Weight (grains)	33
Ballistic Coefficient	0.080
Sectional Density	0.094
COAL Tested	1.680"
Speer Part No.	1014

			START CHARGE		MAXIMUM CHARGE	
Propellant	Case	Primer	Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon H110	Winchester	CCI 500	12.4	3198	12.8	3229
Winchester 296	Winchester	CCI 500	12.4	3054	12.8	3217
Accurate No. 9	Winchester	CCI 500	10.2	2944	10.8	3106
Hodgdon Lil' Gun	Winchester	CCI 500	13.5 C	3068	14.0 C	3093
Alliant 2400	Winchester	CCI 500	11.0	2953	11.5 C	2985
Vihtavuori N110	Winchester	CCI 500	10.0	2879	10.6 C	2947

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load