



270 Weatherby Magnum

.277"	270 Spitzer BTSP	270 Spitzer SP Hot-Cor®	270 Grand Slam® SP
Weight (grains)	130	130	130
Ballistic Coefficient	0.412	0.383	0.332
Sectional Density	0.242	0.242	0.242
COAL Tested	3.250"	3.250"	3.250"
Speer Part No.	1458	1459	1465

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 26	Federal	Federal 215	62.8	2951	69.6	3292
Alliant Reloder 25	Federal	Federal 215	68.0	3080	72.0	3267
Ramshot Magnum	Federal	Federal 215	71.0	3079	75.0	3254
Alliant Reloder 23	Federal	Federal 215	60.4	2962	66.8	3241
Alliant Power Pro 4000-MR	Federal	Federal 215	58.0	2965	64.4	3237
Alliant Reloder 33	Federal	Federal 215	76.3	3044	80.0 C	3228
Vihtavuori N560	Federal	Federal 215	65.0	3030	69.0	3222
IMR 7828	Federal	Federal 215	65.0	3054	69.0	3217
Alliant Reloder 22	Federal	Federal 215	64.0	3048	68.0	3214
Hodgdon Retumbo	Federal	Federal 215	69.0	3026	73.0	3209
IMR 7977	Federal	Federal 215	66.6	2890	73.6	3202
Accurate Magpro	Federal	Federal 215	68.0	3014	72.0	3189
IMR 4831	Federal	Federal 215	60.0	3019	64.0	3181
Alliant Reloder 19	Federal	Federal 215	61.0	3040	65.0	3176
Hodgdon H4831SC	Federal	Federal 215	62.0	2980	66.0	3120

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load