

270 Weatherby Magnum

.277"	270 Spitzer BTSP	270 Spitzer SP Hot- Cor®	270 Grand Slam® SP
Weight (grains)	150	150	150
Ballistic Coefficient	0.489	0.455	0.378
Sectional Density	0.279	0.279	0.279
COAL Tested	3.250"	3.250"	3.260"
Speer Part No.	1604	1605	1608

			START CHARGE		MAXIMUM CHARGE	
Propellant	Case	Primer	Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 33	Federal	Federal 215	70.7	2772	78.3 C	3109
Alliant Reloder 26	Federal	Federal 215	60.0	2780	66.5	3067
Ramshot Magnum	Federal	Federal 215	68.0	2865	72.0	3028
Alliant Reloder 23	Federal	Federal 215	57.4	2778	63.8	3015
Alliant Reloder 50	Federal	Federal 215	72.7	2706	80.0 C	2998
IMR 7977	Federal	Federal 215	62.8	2706	69.6	2989
Hodgdon US 869	Federal	Federal 215	77.0	2862	81.0 C	2987
Hodgdon Retumbo	Federal	Federal 215	64.0	2862	68.0	2980
Alliant Reloder 25	Federal	Federal 215	62.0	2839	66.0	2966
Accurate 8700	Federal	Federal 215	77.0	2832	81.0 C	2957
IMR 7828	Federal	Federal 215	60.0	2803	64.0	2950
Alliant Reloder 22	Federal	Federal 215	59.0	2800	63.0	2942
IMR 4831	Federal	Federal 215	56.0	2759	60.0	2914
Alliant Reloder 19	Federal	Federal 215	56.0	2790	60.0	2903
Hodgdon H4831SC	Federal	Federal 215	58.0	2771	62.0	2903
Vihtavuori N560	Federal	Federal 215	58.0	2771	62.0	2902

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load