

30-40 Krag

.308"	30 Spitzer BTSP	30 Spitzer SP Hot-Cor®	30 Grand Slam® SP/CANN
Weight (grains)	165	165	165
Ballistic Coefficient	0.520	0.444	0.354
Sectional Density	0.266	0.266	0.266
COAL Tested	3.089"	3.089"	3.089"
Speer Part No.	2034	2035	2038

			START CHARGE		MAXIMUM CHARGE	
Propellant	Case	Primer	Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
IMR 4064	Winchester	CCI 200	37.0	2098	41.0	2339
IMR 4831	Winchester	CCI 200	44.0	2115	48.0	2311
Hodgdon H380	Winchester	CCI 250	40.0	2032	44.0	2279
Hodgdon H414	Winchester	CCI 250	43.0	2044	47.0	2279
IMR 4350	Winchester	CCI 200	44.0	2057	48.0	2258
IMR 4895	Winchester	CCI 200	34.0	1946	38.0	2243
Hodgdon H322	Winchester	CCI 200	30.0	1818	34.0	2099
IMR SR 4759 (reduced load)	Winchester	CCI 200	22.0	1639	24.0	1812

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load