

300 AAC Blackout

.308"	30 Spitzer BTSP	30 Spitzer SP Hot-Cor®	30 Grand Slam® SP/CANN
Weight (grains)	180	180	180
Ballistic Coefficient	0.545	0.441	0.374
Sectional Density	0.271	0.271	0.271
COAL Tested	2.170"	2.170"	2.170"
Speer Part No.	2052	2053	2063

			START CHARGE		MAXIMUM CHARGE	
Propellant	Case	Primer	Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Accurate 5744	Lake City	Federal 205	15.5	1514	17.0 C	1693
Alliant Power Pro 300-MP	Lake City	Federal 205	14.2	1510	15.5	1617
Vihtavuori N110	Lake City	Federal 205	12.7	1488	14.1 C	1608
Ramshot Enforcer	Lake City	Federal 205	12.6	1513	13.7	1604
IMR 4227	Lake City	Federal 205	14.3	1463	15.8 C	1599
IMR 4198	Lake City	Federal 205	15.5 C	1439	16.4 C	1563
Accurate No. 9	Lake City	Federal 205	11.0	1397	12.3	1528

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

 $\textit{Maximum loads should be used with CAUTION} ~ \textbf{\textit{C}} = \textit{Compressed Load}$