



300 AAC Blackout

.308"	30
	GD
Weight (grains)	150
Ballistic Coefficient	0.463
Sectional Density	0.226
COAL Tested	2.180"
Speer Part No.	308150BLKGDB

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon Li' Gun	Lake City	Federal 205	20.0	2057	21.0 C	2154
Accurate 5744	Lake City	Federal 205	17.6	1787	20.1 C	2041
Vihtavuori N110	Lake City	Federal 205	15.1	1805	16.8 C	1961
Allaint Power Pro 300-MP	Lake City	Federal 205	17.2	1786	19.0	1960
Accurate 1680	Lake City	Federal 205	20.5	1785	22.0 C	1934
Ramshot Enforcer	Lake City	Federal 205	15.5	1792	17.1	1932
IMR 4227	Lake City	Federal 205	17.2	1746	18.8 C	1922
Hodgdon H110	Lake City	Federal 205	15.7	1747	17.8	1915
Vihtavuori N120	Lake City	Federal 205	18.0	1737	19.5 C	1894
Accurate No 9	Lake City	Federal 205	12.7	1671	14.1	1818

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load