

300 Remington Short Action Ultra Magnum

| .308" | 30 SPFN | 30 Spitzer BTSP | 30 Spitzer SP Hot-Cor® | 30 Grand Slam® SP |
|-----------------------|------------|-----------------------|------------------------------|-------------------------|
| Weight (grains) | 150 | 150 | 150 | 150 |
| Ballistic Coefficient | 0.255 | 0.417 | 0.377 | 0.295 |
| Sectional Density | 0.226 | 0.226 | 0.226 | 0.226 |
| COAL Tested | 2.680" | 2.800" | 2.800" | 2.680" |
| Speer Part No. | 2011 | 2022 | 2023 | 2026 |

| | | | START CHARGE | | MAXIMUM CHARGE | |
|------------------------------|-----------|---------|-----------------|-------------------------------|-----------------|----------------------------|
| Propellant | Case | Primer | Weight (grains) | Muzzle Velocity (feet/sec) | Weight (grains) | Muzzle Velocity (feet/sec) |
| Vihtavuori N560 | Remington | CCI 200 | 69.0 | 3030 | 73.0 C | 3210 |
| Winchester 760 | Remington | CCI 250 | 64.0 | 3041 | 68.0 | 3194 |
| Accurate 4350 | Remington | CCI 200 | 64.0 | 2974 | 68.0 C | 3173 |
| IMR 4831 | Remington | CCI 200 | 65.0 | 2963 | 69.0 C | 3158 |
| Hodgdon H414 | Remington | CCI 250 | 62.0 | 3004 | 66.0 | 3158 |
| Hodgdon H4350 | Remington | CCI 200 | 62.0 | 2969 | 66.0 | 3152 |
| IMR 4350 | Remington | CCI 200 | 63.0 | 2981 | 67.0 | 3150 |
| Alliant Reloder 19 | Remington | CCI 200 | 67.0 | 2969 | 71.0 C | 3150 |
| Accurate 2700 | Remington | CCI 250 | 60.0 | 2963 | 64.0 | 3106 |
| Hodgdon Varget | Remington | CCI 200 | 54.0 | 2913 | 58.0 | 3088 |
| Hodgdon H4831SC | Remington | CCI 200 | 67.0 | 2910 | 71.0 C | 3072 |
| Accurate 5744 (reduced load) | Remington | CCI 200 | 28.0 | 1922 | 30.0 | 2039 |

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load