



300 Remington Ultra Magnum

.308"	30 SPFN Hot-Cor®	30 Spitzer BTSP	30 Spitzer SP Hot-Cor®	30 Grand Slam® SP
Weight (grains)	150	150	150	150
Ballistic Coefficient	0.255	0.417	0.377	0.295
Sectional Density	0.226	0.226	0.226	0.226
COAL Tested	3.365"	3.495"	3.495"	3.460"
Speer Part No.	2011	2022	2023	2026

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Vihtavuori N560	Federal	Federal 215	93.0	3308	97.0	3442
Alliant Reloder 22	Federal	Federal 215	93.0	3283	97.0	3437
Alliant Reloder 33	Federal	Federal 215	97.5	3078	108.3 C	3437
Ramshot Magnum	Federal	Federal 215	100.0	3293	104.0	3425
IMR 7828	Federal	Federal 215	93.0	3246	97.0	3419
Alliant Reloder 26	Federal	Federal 215	83.4	3102	92.4	3417
Alliant Power Pro 4000-MR	Federal	Federal 215	79.0	3093	87.5	3404
IMR 7977	Federal	Federal 215	90.0	3031	99.2	3402
Alliant Reloder 19	Federal	Federal 215	90.0	3261	94.0	3401
Accurate 3100	Federal	Federal 215	90.0	3257	94.0	3388
Alliant Reloder 23	Federal	Federal 215	81.7	3059	90.4	3383
IMR 4831	Federal	Federal 215	87.0	3217	91.0	3372
Hodgdon H4831SC	Federal	Federal 215	92.0	3205	96.0	3335

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load