



## 338 Federal

<b>.338"</b>	<b>338</b>
	<b>Spitzer SP Hot-</b>
	<b>Cor®</b>
<b>Weight (grains)</b>	200
<b>Ballistic Coefficient</b>	0.426
<b>Sectional Density</b>	0.250
<b>COAL Tested</b>	2.820"
<b>Speer Part No.</b>	2405

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Power Pro Varmint	Federal	Federal 210	44.6	2499	<b>49.6</b>	2708
Hodgdon CFE 223	Federal	Federal 210	46.1	2478	<b>51.0 C</b>	2682
Alliant AR-Comp	Federal	Federal 210	41.8	2458	<b>46.3</b>	2655
IMR 8208 XBR	Federal	Federal 210	41.8	2417	<b>46.3</b>	2625
Alliant Reloder 15	Federal	Federal 210	44.0	2508	<b>46.0 C</b>	2598
Alliant Power Pro 1200-R	Federal	Federal 210	38.0	2393	<b>42.2</b>	2579
Hodgdon Varget	Federal	Federal 210	45.0	2485	<b>47.0 C</b>	2571
Winchester 748	Federal	Federal 210	45.5	2504	<b>47.5</b>	2570
Accurate LT-32	Federal	Federal 210	38.2	2342	<b>42.2</b>	2528
Ramshot TAC	Federal	Federal 210	42.0	2421	<b>44.0</b>	2504
Hodgdon H322	Federal	Federal 210	38.0	2303	<b>40.0</b>	2451
Alliant Reloder 10X	Federal	Federal 210	36.5	2345	<b>38.5</b>	2444
Accurate 2015	Federal	Federal 210	38.0	2303	<b>40.0</b>	2404
Alliant Reloder 7	Federal	Federal 210	34.5	2306	<b>36.5</b>	2403
IMR 4198	Federal	Federal 210	33.5	2268	<b>35.5</b>	2368

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*