



41 Remington Magnum

.410"	41
Weight (grains)	210
Ballistic Coefficient	0.183
Sectional Density	0.178
COAL Tested	1.575"
Speer Part No.	4430

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon H110	Winchester	CCI 350	20.5	1707	21.5	1783
Winchester 296	Winchester	CCI 350	20.5	1687	21.5	1782
Alliant 2400	Winchester	CCI 300	18.0	1603	19.0	1702
Vihtavuori N110	Winchester	CCI 300	17.0	1576	18.0	1692
Accurate No. 9	Winchester	CCI 300	17.0	1571	18.0	1656
IMR 4227	Winchester	CCI 300	21.0	1471	22.0	1580
Alliant Unique	Winchester	CCI 300	8.7	1186	9.7	1315
Vihtavuori N350	Winchester	CCI 300	9.8	1235	10.5	1297

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load