



444 Marlin

.429"	44
Weight (grains)	DCSP
Ballistic Coefficient	270
Sectional Density	0.193
COAL Tested	0.210
Speer Part No.	2.545"
	4461

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Vihtavuori N133	Remington	CCI 200	50.0	2089	54.0 C	2256
Alliant Reloder 7	Remington	CCI 200	43.0	2034	47.0	2216
Alliant Reloder 10X	Remington	CCI 200	46.0	2042	50.0	2212
IMR 8208 XBR	Hornady	CCI 200	51.0	2041	53.6	2155
Hodgdon H322	Remington	CCI 200	46.0	1961	50.0	2148
Hodgdon BENCHMARK	Remington	CCI 200	47.0	1969	51.0	2134
Accurate 2015	Remington	CCI 200	47.0	1948	51.0	2114
IMR 4895	Remington	CCI 200	50.0	1904	54.0 C	2062
IMR 4198	Remington	CCI 200	36.0	1882	40.0	2052
Ramshot X-Terminator	Remington	CCI 250	46.0	1883	50.0	2028

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load