

## 44 Remington Magnum (Rifle)

.429"	44 GDHP
Weight (grains)	210
Ballistic Coefficient	0.154
Sectional Density	0.163
COAL Tested	1.600"
Speer Part No.	4428

			START CHARGE		MAXIMUM CHARGE	
Propellant	Case	Primer	Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon Lil' Gun	Winchester	CCI 350	26.5	2067	28.5	2128
Hodgdon H110	Winchester	CCI 350	25.5	1892	27.5	2036
Winchester 296	Winchester	CCI 350	25.5	1907	27.5	2030
Ramshot Enforcer	Winchester	CCI 350	23.0	1857	25.0	1972
Vihtavuori N110	Winchester	CCI 300	21.0	1740	23.0	1927
Alliant 2400	Winchester	CCI 300	21.5	1739	23.5	1898
Accurate No. 9	Winchester	CCI 300	21.0	1775	23.0	1891
Alliant Power Pistol	Winchester	CCI 300	12.5	1515	14.5	1725
Alliant Unique	Winchester	CCI 300	10.5	1301	12.5	1513
Hodgdon H. Universal	Winchester	CCI 300	9.0	1155	11.0	1395

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load