

45-70 Government (Strong Actions)

.458"	45 SPFN
Weight (grains)	400
Ballistic Coefficient	0.259
Sectional Density	0.272
COAL Tested	2.540"
Speer Part No.	2479

			START CHARGE		MAXIMUM CHARGE	
Propellant	Case	Primer	Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
IMR 8208	Winchester	CCI 200	58.0	1961	62.0	2107
Hodgdon BENCHMARK	Winchester	CCI 200	57.0	1969	61.0	2102
Accurate 2015	Winchester	CCI 200	52.0	1857	56.0 C	2029
Hodgdon H4895	Winchester	CCI 200	56.0	1836	60.0 C	2007
/ihtavuori N133	Winchester	CCI 200	51.0	1837	55.0	2005
Hodgdon H335	Winchester	CCI 250	58.0	1844	62.0 C	1964
MR 4166	Winchester	CCI 200	54.0	1813	58.2	1951
Hodgdon H322	Winchester	CCI 200	51.0	1724	55.0	1935
Alliant Reloder 10X	Winchester	CCI 200	47.0	1774	51.0	1929
MR 4198	Winchester	CCI 200	42.0	1631	46.0	1819
MR 3031	Winchester	CCI 200	50.0	1565	54.0 C	1790
MR 4064	Winchester	CCI 200	52.0	1601	56.0 C	1764
MR 4320	Winchester	CCI 200	53.0	1615	57.0	1761
MR SR 4759(reduced load))	Winchester	CCI 200	28.0	1349	32.0	1533

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load