



speer
bullets

6.5 Grendel

.264"	6.5mm
Weight (grains)	TNT® HP
Ballistic Coefficient	90
Sectional Density	0.281
COAL Tested	0.184
Speer Part No.	2.190"
	1445

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
IMR 8208 XBR	Federal	Federal 205	28.7	2721	31.7 C	3013
Alliant Power Pro Varmint	Federal	Federal 205	30.1	2723	33.2	3009
Hodgdon H335	Federal	Federal 205	29.0	2745	32.0	3009
Accurate 2200	Federal	Federal 205	26.4	2732	29.2	2992
Accurate 2230	Federal	Federal 205	27.8	2731	30.7	2965
Alliant Power Pro 1200-R	Federal	Federal 205	26.5	2734	29.2	2964
Hodgdon Benchmark	Federal	Federal 205	28.2	2667	31.2	2952
Alliant Reloder 10X	Federal	Federal 205	25.9	2640	28.6	2916
Vihtavuori N135	Federal	Federal 205	27.7	2673	30.4 C	2910
Winchester 748	Federal	Federal 205	30.2	2670	33.2 C	2907
Alliant AR-Comp	Federal	Federal 205	28.8	2774	30.3 C	2898
IMR 3031	Federal	Federal 205	27.2	2621	29.4 C	2848

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load