DATAFILE™

7mm-08 Remington

.284"	7mm Spitzer SP Hot-Cor®	7mm Spitzer BTSP
Weight (grains)	130	130
Ballistic Coefficient	0.368	0.424
Sectional Density	0.230	0.230
COAL Tested	2.730"	2.730"
Speer Part No.	1623	1624

			START CHARGE		MAXIMUM CHARGE	
Propellant	**Case**	**Primer**	**Weight (grains)**	**Muzzle Velocity (feet/sec)**	**Weight (grains)**	**Muzzle Velocity (feet/sec)**
IMR 4064	Remington	CCI 200	41.0	2835	**45.0**	3065
IMR 4350	Remington	CCI 200	46.0	2766	**50.0**	3006
Hodgdon H4350	Remington	CCI 200	46.0	2715	**50.0 C**	2984
Alliant Reloder 16	Federal	Federal 210	42.6	2708	**47.3 C**	2984
Winchester 760	Remington	CCI 250	45.0	2727	**49.0**	2980
Hodgdon H414	Remington	CCI 250	45.0	2673	**49.0**	2954
Ramshot Big Game	Federal	Federal 210	42.1	2764	**45.9**	2950
Alliant Power Pro 2000-MR	Federal	Federal 210	39.4	2690	**43.5**	2923
Accurate 4350	Federal	Federal 210	44.3	2644	**49.0 C**	2900
Hodgdon H380	Remington	CCI 250	44.0	2652	**48.0**	2898
Hodgdon Varget	Remington	CCI 200	39.0	2641	**43.0**	2888
IMR 3031	Remington	CCI 200	38.0	2684	**42.0**	2886
Alliant Power Pro Varmint	Federal	Federal 210	36.4	2648	**40.5**	2884
Alliant Reloder 17	Federal	Federal 210	41.7	2644	**45.9**	2882
IMR 4831	Remington	CCI 200	46.0	2678	**50.0 C**	2880
Hodgdon CFE 223	Federal	Federal 210	36.5	2570	**41.1**	2868
Alliant AR-Comp	Federal	Federal 210	35.8	2697	**38.8**	2857
Vihtavuori N140	Remington	CCI 200	38.0	2531	**42.0**	2812
Hodgdon H335	Remington	CCI 250	37.0	2607	**41.0**	2788
Alliant Reloder 15	Remington	CCI 200	38.0	2577	**42.0**	2786
Accurate 2520	Remington	CCI 250	34.0	2409	**38.0**	2662

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load